MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910,1200 and OSHA Form 174

IDENTITY AND DIST	RIBUT	OR'S INFORMATIO	V				
PA Rating: Health-2; Flammability-0; Reactivity-0; Special-0 HMIS Rating: Health-2; Flammability-0; Reactivity-0; Personal Protection-B							
Manufactured For: EARTHENAIR		T Hazard Classifica					
Address: 3535 Northcliffe Road	lde	ntity (trade name as used on label): D & S Vending, Inc. Penetrating					
Address: Cleveland Heights, OH 44118	Lubi	Lubricant			-/		
		MSDS Number: 390 Revision- 17					
		Date Prepared: 10/11/95 Prepared By: DL					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		mation Calls: (770)422					
SECTION 1 - MATERIAL IDE	MITIC	CAS Number	SARA	OSHA PEL	ACGIH	Cassinosan	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CV2 Millings	III LIST	(ppm)	TLV (ppm)	Carcinogen Ref. Source *	
TRICHLOROETHYLENE		79-01-6	Yes	50	50	ь	
PERCHLOROETHYLENE		127-18-4	Yes	25	25	a,b	
PETROLEUM DISTILLATE		64742-54-7	Yes	5mg\M3	5mg\M3	d	
BARIUM PETROLEUM SULFONATE		61760-48-5	Yes	5mg\M3	5mg\M3	d	
				3			
WARNING: This product contains a chemical or chemicals know the State of California to cause cancer.	vn to						
SECTION 2 PHYSICAL /C	LIESZI	TAL CHARACTERIS	TICE		** · · · · · · · · · · · · · · · · · ·		
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 1.44							
Bolling Point: N/A Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Deneity (Air = 1): N/E		Evaporation Rate (n-butyl acetate= 1): 2.1 (concentrate only)					
Solubility in Water: Insoluble	Water Reactive: No						
Appearance and Odor: Light brown odor with chloringled solvent odor.							
SECTION 3 - FIRE AND	EXPL	OSION HAZARD DA	TA			· · · · · · · · · · · · · · · · · · ·	
FLAMMABILITY as per USA FLAME PROJECTION TEST A		nition Temperature	Flamm			in Volume:	
(aerosois) NON-FLAMMABLE FLASH POINT AND METHOD USED (non-aerosois): N/A	EVT	N/E INGUISHER MEDIA: F	% LEL			L: N/E	
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatu	8.				on alloxide.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures	above	130°F or the container	nay ruptur	8.		_	
SECTION 4 - REAC							
STABILITY [X] STABLE [] UNSTABLE Incompatibility (Mat. to avoid): Reactive metals, aluminum, magnesium, strong	HAZ Con	ARDOUS POLYMERIZ ditions to Avoid: Oper	ATION [flame, we	WILL ()	() WILL NOT at.	OCCUR	
oxidizing agents.			253	-			
Hazardous Decomposition Products: CO2, CO, HCI, small amounts of phosgene and chlorine.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Irritation due to defatting of skin.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. CHRONIC EFFECTS:(Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spieen, lung or brain damage,							
cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously occurring malignant tumors in certain laboratory rats and mice.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water.	iet lmm	ediate medical attention					
SECTION 6 - CONTROL A	ND PR	OTECTIVE MEASU	RES				
Respiratory Protection (specify type): If vapor concentration exceeds TLV, us	e respi	rator approved by U.S.	Bureau of	Mines for orga	anic vapor.		
Protective Gloves: Neoprene gloves recommended.	Eye	Protection: Safety glas	ses recom	mended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration by							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material is Spilled Or Released: Absorb with suitable nevaporate if small spill. DO NOT FLUSH TO SEWER.	nedium.	Incinerate or landfill ac	cording to	local, state or	f-ederal regu	lations. Allow to	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure	through	normal use, pose no di	sposal haz	ard.			
Precautions To Be Taken in Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hezards: KEEP OUT OF REACH OF CHILDREN, Avoid food contamination. Avoid inhalation of vapors.							
Was believe the statements technical information and recommendations contained bearing are ediable, but thousand allow without was maked and any lived							

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only