

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 559

IDENTITY: D&S VENDING GASKET (FC)20

Revision Date: 07/30/2004

Section I

Manufacturer's Name: EARTHENAIR, INC.

Address: 5049 BRISTOL CT

CLEVELAND HTS

State: OH Zip Code: 441242533

Telephone Numbers:

Emergency:

800/255-3924

Information:

216/691-8957

HMIS CODES: REACTIVITY: 2 FLAMMABILITY: 1 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name		Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
METHYL ALCOHOL	*	67-56-1	200 PPM	250 PPM	N/A	—
METHYLENE CHLORIDE	*+	75-09-2	25 PPM	25 PPM	N/A	—
PROPANE/N-BUTANE		68476-86-8	1000 PPM	600 PPM	N/A	—

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	104F	Specific Gravity (water=1)	1.23
Vapor Pressure(mm Hg)	100	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	15%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR SPRAY, CHLORINATED SOLVENT ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): NONE Flammable Limits: LEL: N/A UEL: N/A
 Extinguishing Media: CO2, FOAM, WATER, DRY CHEMICAL
 Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.
 EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.