MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTI	RIBUTOR'S INFORMAT	TION				
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special	HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B					
Manufactured For: Earthenair Inc.	DOT Hazard Classification: ORM-D					
Address:	Identity (trade name as used on label): D & S Adhesive 1115					
Address:						
Phone:	MSDS Number: A00315 Revision- 11					
MERGENCY RESPONSE NUMBER: Date Prepared: 10/28/05 Prepared By: IB/TR						
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ACETONE	67-64-1	No	1000	750	d	
HEPTANE	142-82-5	No	500	400	d	
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d	
	74-98-6	No	1000	1000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.853						
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.80	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E Water Reactive: No					
Solubility in Water: Partial Water Reactive: No Appearance and Odor: Straw colored liquid with ketone solvent odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
LAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
(aerosols) EXTREMELY FLAMMABLE	N/E % LEL: N/E % UEL: N/E					
FLASH POINT AND METHOD USED (non-aerosols): N/A	SPECIAL FIRE FIGHTING					
(3.00.00)	water fog to cool containers to prevent rupturing & exploding containers. Provide					
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. shielding for personnel.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT						
OCCUR						
Incompatibility (Mat. to avoid): Strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat, sparks.						
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible						
unconsciousness or asphyxiation.						
Eye Contact: Irritation. Skin Contact: Irritation due to defatting of skin.						
Ingestion: Possible chemical pneumonitis if aspirated into lungs.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of solvents may cause brain and						
other nervous system damage.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode.						
Protective Gloves: Neoprene. Eye Protection: Safety glasses recommended.						
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Stone To Be Taken If Metavial to Smithed On Belegged. About with quitable medium, Inginerate as landfill according to lead, state or fodoral.						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove						
ignition sources.						